

New!

DP30 Doors

Exterior Doors from Upstate Door

Now our Distinctive Exterior Door Solutions are available to meet your building code requirements for home safety and property protection.

These Exterior Doors meet the following specification:

- ◆ DP30
- ◆ Inswing design
- ◆ Certified by Keystone Certification for structural performance

Visit our exterior gallery on our web site or the exterior door section of our catalog for just some of the Upstate Door DP30 and Impact Resistant Rated Door options.

Call or Email our Custom Door Experts to assist you.

TECHNICAL SPECIFICATIONS

LAYOUTS

- Single Door
- Double Door

MAX. SIZES

- Overall: 7' 1 1/2" x 8' 2 1/2"
- Door: 3'6" x 8'0"

DOOR

- Inswings only
- 1 3/4" min. door
- Stile width: 4" min.
- Top Rail: 4" min.
- Knob Rail: 5" min.
- Bottom Rail: 7" min.
- Center Rail/Stile limitations: None
- Single Units: Double cylinder bore centered @ 36" & 41 1/2" from bottom of door
- Double Units: Double cylinder bore centered @ 36" & 41 1/2" from bottom of door (*active door*) with T-astragal, 1 pair of Baldwin flush bolts installed into inactive door, Emtek surface applied flush bolts

WOOD SPECIES

- Genuine Mahogany
- African Mahogany
- Spanish Cedar
- White Oak
- Douglas Fir
- Teak

GLASS

- Min. 1/4" clear or 1/2" insulated safety glass
- All glass cuts must be SDL

FRAME

- Jamb
 - ▶ 1 1/4" thick rabbeted jamb, kerfed with Q-lon
 - ▶ Jamb width: 4 9/16" min.
- 1 3/4" Mahogany or White Oak sill

